

Self-contained luminaire

SV EURO 4 ... 4L






SV EURO 4 with pictogram PR





SV EURO 4L with pictogram PR

Dimensions in mm



SV EURO 4



SV EURO 4L

- Compact self-contained exit or escape luminaire
- Foil unit with test button for function test and green LED for charging control
- Luminaire of high quality, UV-resistant, halogen-free plastic
- **SV EURO 4:**
With transparent cover as single-sided exit luminaire for wall mounting oder as safety luminaire for escape route illumination
- **SV EURO 4L:**
With transparent cover as universal used exit luminaire with 3-sided light emission
- Cover with simple snap mounting and pictogram foil set
- Optional IP54 set for increased sealing requirements for indoor rooms
- Luminaire is generally suitable for maintained or non-maintained mode

Viewing distance	17 m
Luminous flux Φ_E / Φ_{Nenn} at end of rated operating time	40 %
Housing material	Plastic
Housing colour	RAL 7035 (grey)
Weight	1.35 kg
Type of mounting	EURO 4: Wall or ceiling mounting EURO 4L: Ceiling, chain or wall bracket mounting
Terminals	for 2,5 mm ²
Connection voltage	230 V, 50 Hz
Power consumption mains operation	16 VA
Permissible ambient temperature	Maintained mode -5 °C to +30 °C Non-maintained mode 0 °C to +35 °C
Battery	rechargeable, maintenance free and gas tight NC-Accu, Duration of emergency lighting 3 h: 3.6 V / 4.0 Ah
Light source	8 W/T16, 450 lm

Ordering details

Type	Scope of supply	Order No.
SV EURO 4-3/D (SET) acc. to ISO 7010	Luminaire enclosure incl. cover 3 self-adhesive legend foils PR, PL, PU and test button 	40071354770

SV EURO 4L-3/D (SET) acc. to ISO 7010	Luminaire enclosure incl. cover 3 self-adhesive legend foils PR, PL, PU and test button 	40071354771
------------------------------------------	------------------------------------------------------------------------------------------------	-------------

Accessories

Type	Order No.
Wall bracket	40071350668
Chain fastening	40071350669
IP 54 Option	40071350670




Chain fastening



Wall bracket

Self-contained luminaire

SV EURO 4 ... 4L



**Polar curve SV EURO 4
with clear cover**

Planning help for SV EURO 4 for E = 1.0 lx (0.5 lx) with transparent cover

Measuring level 0.02 m. maintenance factor MF = 80 %. battery operation. distances in m

Mounting height (m)	Types of mounting	L1	L2	L3	L4
2.5	Ceiling mounting	2.0 (2.7)	5.4 (6.8)	2.9 (4.2)	8.4 (11.4)
3.0	Escape route centre	1.9 (2.8)	5.6 (7.2)	2.9 (4.2)	8.4 (11.8)
4.0		1.1 (2.7)	5.4 (7.8)	2.2 (4.1)	8.2 (11.8)
5.0		– (2.2)	4.4 (7.8)	– (3.7)	7.4 (11.6)
6.0		– (0.5)	2.0 (7.2)	– (1.8)	3.6 (11.4)
7.0		– (–)	2.0 (6.0)	– (–)	2.0 (10.4)
2.0	Wall mounting	2.1 (2.7)	5.4 (6.8)	2.5 (3.7)	7.4 (10.0)
2.5		2.2 (3.0)	6.0 (7.6)	– (3.7)	7.4 (10.4)
3.0		2.2 (3.1)	6.2 (8.2)	– (–)	7.0 (10.6)