



GuideLed FSL 10011, 10012, 10013 CG-S


Surface mounting or semi-recessed mounting



GuideLed FSL CG-S



FSL 10011 CG-S



FSL 10012/10013 CG-S

GuideLed FSL 10011, 10012, 10013 CG-S

- Safety luminaire in LED technology for surface mounting or semi-recessed mounting
- Low height of only 36 mm or 14 mm
- Anti-glare illumination ensured by precise micro-prism optics
- Increased safety by use of 3-chip LEDs
- Reduced battery costs on account of especially low power consumption
- Low operating costs on account of low effective power of 4 W only
- Suitable for mounting height of up to 5.5 m
- Minimum service requirement due to high service life of the LEDs (50,000 hours)
- Installation of safety luminaire without the use of tools at the mounting set


Luminous flux Φ_N	125 lm
Luminous flux Φ_E/Φ_N at the end of rated operating time	100%
Housing material	PC, PMMA
Housing colour	Light grey RAL 7035
Weight	0.49 kg (10011 FSL CG-S) 0.45 kg (10012 FSL CG-S)
Type of mounting	Ceiling installation / semi-recessed installation
Connection terminal	Clamp terminal 2.5 mm ²
Voltage ranges	220 - 240 V AC, 50/60 Hz 176 - 275 V DC
Current consumption - battery operation (220 V)	18 mA
Power consumption mains operation (apparent power / effective power)	7.2 VA / 4.0 W
Permissible ambient temperature	-20 °C to +40 °C
Light source	LED batten with 3-chip LEDs

Ordering details fastening set and safety luminaire module

Scope of supply	Order No.
Mounting set for GuideLed FSL 10011 CG-S, surface installation, incl. LED supply and CG-S technology (20 addresses)	40071353641
Mounting set for GuideLed FSL 10012 CG-S, recessed installation of the V-CG-SLS28 supply provided and CG-S technology (20 addresses) *	40071353642
Mounting set for GuideLed FSL 10013 CG-S, recessed installation of the V-CG-SLR28 supply provided and CG-S technology (20 addresses) *	40071353644
LED safety luminaire GuideLed FSL 10011 / 10012 CG-S with special micro-prism optics (without mounting set)	40071353590

* Installation of the LED supply in a not included device, for further information about the LED supply please visit www.ceag.de.

Surface mounting or semi-recessed mounting



Measuring height 0.02 m, maintenance factor MF = 80%, battery operation

1