29011 LED with cover PR





Style Variant 29011 LED CG-S

- Single-sided LED escape sign luminaire of high quality, UV-resistant, halogen-free plastic
- Large selection of screenprinted pictogram covers with simple snap mounting
- Minimum service requirement due to high service life of the LEDs (50,000 hours)
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditures by STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit

1

Viewing distance	32 m
Luminous flux Φ_E/Φ_N at the end of rated operating time	100 %
Housing material	Polycarbonate (850 °C glow wire resistant)
Weight incl. cover	1.1 kg
Housing colour	Grey
Type of mounting	Wall mounting
Connection terminals	Clamp terminal 2.5 mm²
Connection voltage	220 - 240 V, 50/60 Hz, 176 - 275 V DC
Current consumption - battery operation (220 V)	19 mA
Power consumption mains operation (apparent power / effective power)	7.6 VA / 4.4 W
Permissible temperature range	-10 °C ... +40 °C
Light source	HighPower LEDs 3 x 1.1 W

Ordering details

Type	Scope of supply		Order No.
29011 LED CG-S	Luminaire housing without cover, with CEWA GUARD monitoring and 20-digit address switch		40071350551
Cover PL acc. to ISO 7010	Cover with silkscreened pictogram		40071354130
Cover PR acc. to ISO 7010	Cover with silkscreened pictogram		40071354131
Cover PU acc. to ISO 7010	Cover with silkscreened pictogram		40071354132

Accessories

Scope of supply	Order No.
Wire guard AP	40071348370